



# F-500 EA<sup>®</sup> FIRE EXTINGUISHER

Powered by  
HCT's Fluorine-Free  
Encapsulator Technology



## Engineered Advantage

The F-500 EA<sup>®</sup> Fire Extinguisher provides unmatched incipient fire protection and flammable spill control in a small package. This stainless steel unit is effective on a variety of hazards, including polar and non-polar fuels. A single charge can encapsulate a half-gallon spill in minutes.

## Nominal Measurements

Capacity	2.5 G
Dimensions	22.5 IN X 7 IN
Weight (Empty)	7.5 LBS
Flow Time	45 SEC
Working Pressure	150 PSI

Hazard Control Technologies, Inc.

150 WALTER WAY, FAYETTEVILLE, GEORGIA 30214 / +1 770 719 5112 / INFO@HCT-WORLD.COM / HCT-WORLD.COM

# APPLICATIONS

**Class A Hazards  
Common Materials**

MN  
SB

**Class B Hazards  
Flammable Liquids**

MN  
SB

**Class D Hazards  
Combustible Metals**

MN

**Class K Hazards  
Oils and Fats**

MN

**Lithium-ion Hazards  
Rechargeable Devices**

MN  
SB

## Firefighting



## Fire Protection



## Select an Assembly

**Misting Nozzle (MN)  
Straight Bore (SB)**

For unmatched versatility, we recommend our Misting Nozzle (MN), and for expert Class A applications that demand a greater distance, our Straight Bore (SB) is ideal.

## How to Order

**Part # F5 FE 9.7L-SS-NB-MN  
Part # F5 FE 9.7L-SS-NB-SB**

The F-500 EA® Fire Extinguisher is sold unfilled. F-500 EA® Recharge Kits are sold separately. For refilling F-500 EA® Fire Extinguishers in bulk, use a 5-gallon pail of F-500 EA®.

Hazard Control Technologies, Inc.

150 WALTER WAY, FAYETTEVILLE, GEORGIA 30214 / +1 770 719 5112 / INFO@HCT-WORLD.COM / HCT-WORLD.COM