F-500 EA®
Fire Extinguisher

Powered by NFPA 18A
Encapsulator Technology



Request Quote

Engineered Advantage

The F-500 EA® Fire Extinguisher provides unmatched incipient fire protection and flammable spill control in a small package. This stainless steel unit is effective on a variety of hazards, including polar and non-polar fuels. A single charge can encapsulate a half-gallon spill in minutes.

Nominal Measurements

Capacity	9.5 L (2.5 G)
Dimensions	571.5 X 178 MM (22.5 X 7 IN)
Weight	3.4 KGS (7.5 LBS)
Flow Time	45 SEC
Working Pressure	10 BAR (150 PSI)

Hazard Control Technologies, Inc.
150 WALTER WAY, FAYETTEVILLE, GEORGIA 30214 / +1 770 719 5112 / INFO@HCT-WORLD.COM / HCT-WORLD.COM

F-500 EA® Applications

Class A Hazards
Common Materials

Class B Hazards
Flammable Liquids

Class D Hazards
Combustible Metals

Class K Hazards
Oils and Fats

Class L Hazards
Lithium-ion Batteries

Firefighting



Fire Protection



How to Use

Misting Nozzle (MN)
Straight Bore (SB)

For unmatched versatility, we recommend our Misting Nozzle (MN), and for expert Class A applications that demand a greater distance, our Straight Bore (SB) is ideal.

How to Order

Part # F5 FE 9.7L-SS-NB-MN
Part # F5 FE 9.7L-SS-NB-SB

The F-500 EA® Fire Extinguisher is sold unfilled. F-500 EA® Recharge Kits are sold separately. For refilling F-500 EA® Fire Extinguishers in bulk, use a 5-gallon pail of F-500 EA®.

Hazard Control Technologies, Inc.
150 WALTER WAY, FAYETTEVILLE, GEORGIA 30214 / +1 770 719 5112 / INFO@HCT-WORLD.COM / HCT-WORLD.COM