F-500 EA®
LIBerator™ Fire Cart

Powered by NFPA 18A
Encapsulator Technology



Request Quote

Engineered Advantage

The F-500 EA® Fire Cart provides advanced incipient fire protection and flammable spill control at a higher capacity in an industrial environment. This tool allows trained personnel to respond to emergencies instantly and aggressively to prevent incident escalation and fire spread.

Nominal Measurements

Capacity	98 L (26 G)
Weight	73 KGS (160 LBS)
Flow Rate	200 LPM (50 GPM)
Flow Time (1%)	52 MIN
Flow Time (3%)	17 MIN

Hazard Control Technologies, Inc.
150 WALTER WAY, FAYETTEVILLE, GEORGIA 30214 / +1 770 719 5112 / INFO@HCT-WORLD.COM / HCT-WORLD.COM

F-500 EA® Applications

Class A Hazards
Common Materials

Class B Hazards
Flammable Liquids

Class D Hazards
Combustible Metals

Class K Hazards
Oils and Fats

Class L Hazards
Lithium-ion Batteries

Firefighting



Fire Protection



How to Use

Connect
Connect the unit to a water supply.

Prepare
Open the valve, extend the hose, and open the nozzle fully until the stream is milky.

Direct
Sweep the stream to cover the entire fire.

How to Order

Part # F500-FC-26G-SS-NA

The F-500 EA® Fire Cart is sold unfilled. To fill and re-fill the F-500 EA® Fire Cart, F-500 EA® is sold separately in 5-gallon pails, 55-gallon drums, 150-gallon totes, and 175-gallon totes.

Hazard Control Technologies, Inc.
150 WALTER WAY, FAYETTEVILLE, GEORGIA 30214 / +1 770 719 5112 / INFO@HCT-WORLD.COM / HCT-WORLD.COM